

**ADVR7016B-LM-E**  
**2 SATA 8ch Analog HD DVR**



**Features:**

- Support 1080N series non-real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support AHD and TVI;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari);
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**ADVR7016B-LM-E**

**Interface:**

**Parameter:**

	Model	ADVR7016B-LM-E
System	Main processor	Hi3521A
Video	video codec	H.264
	Encode	16*1080N@12fps
	Decode	16*1080N@12fps
	Multi-mode input	Pure Analog: 16*1080N; Mixed: 8*1080N (Analog) ++8*960P (Network) Pure Network: 8*1080P; 16*960P; 4*3M; 4*5M
agreement	onvif	support
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	8ch RCA
	Audio output	1ch RCA
	Alarm input	4
	Alarm output	1
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 6T )
Other	Wireless	3G、WIFI(expand via USB)
	Power	12V/4A
	Weight	About 1.825kg
	dimension	310mm(length)* 298mm(width)*60mm(height)