

ADVR7004T-H 1 SATA 4ch Analog HD DVR



Features:

- Support AHD-H series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE, Chrome, Firefox, Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7004T-H

Interface:

Parameter:

| | | |
|------------------------|-------------------|--|
| | Model | ADVR7004T-H |
| System | Main processor | Huawei Hi 3531 |
| Video | video compression | H.264(High Profile); |
| | Encode | 4*AHD-H |
| | Decode | 4*AHD-H |
| | Multi-mode input | Pure Analog: 4*AHD-H; 4*AHD-M; Mixed: 2*AHD-H(analog)+2*1080P(network); 4*AHD-M (analog) +4*720P (network) ; Pure Network: 4*1080P; 20*960H; 1*1080P+8*720P; |
| Audio | Audio compression | G.711A |
| | Intercom | support |
| Recording and Playback | Record mode | Manual>alarm>motion detection>timing |
| | Playback Channels | 4 |
| Storage and backup | Space occupation | 1080P: 20G~30G/ day*channel 720P: ~20G/ day*channel 960H: 12~20G/ day*channel audio: 691.2M/ day*channel |
| | Backup mode | Network backup、USB HDD, USB writer、SATA writer |
| Interface | Video input | 4 BNC |
| | Video output | 1ch VGA,1ch HDMI |
| | Audio input | 4ch RCA |
| | Audio output | 1ch RCA |
| | Alarm input | 0 |
| | Alarm output | 0 |
| | Network interface | RJ45 10M/100M Adaptive Ethernet port |
| | PTZ control | One RS485; support multiple PTZ protocols |
| | USB | 2 USB ports |
| | Hard disk | 1 SATA (Each maximum support 4T) |
| | Wireless | 3G、WIFI(expand via USB) |
| Other | Power | 12V/2A |
| | dimension | 255mm(length)* 236mm(width)* 44mm(height) |