

ADVR7016F-M
 4 SATA 16ch Analog HD DVR
**Features:**

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE, Chrome, Firefox, Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:**ADVR7016F-M****Interface:****Parameter:**

| | Model | ADVR7016F-M |
|------------------------|-------------------|---|
| System | Main processor | Hi 3531+3532 |
| Video | video codec | H.264 |
| | Encode | 16*AHD-M |
| | Decode | 16*AHD-M |
| | Multi-mode input | Pure Analog: 16*AHD-M;16*AHD-L; Mixed:4*AHD-M(Analog)+4*720P(Network); 8*AHD-M(Analog)+8*720P(Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H ; |
| Audio | Audio compression | G.711A |
| | Intercom | support |
| Recording and Playback | Record mode | Manual>alarm>motion detection>timing |
| | Playback Channels | 16(pure local input mode) |
| Storage and backup | Space occupation | 960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel |
| | Backup mode | Network backup、USB HDD, USB writer、SATA writer |
| Interface | Video input | 16 BNC |
| | Video output | 1ch VGA,1ch HDMI |
| | Audio input | 16ch RCA |
| | Audio output | 1ch RCA |
| | Alarm input | 16 |
| | Alarm output | 4 |
| | Network interface | RJ45 10M/100M/1000M Adaptive Ethernet port |
| | PTZ control | One RS485, one RS232; support multiple PTZ protocols |
| | USB | 2 USB ports |
| | Hard disk | 4 SATA (Each maximum support 4T) |
| | Wireless | 3G、WIFI(expand via USB) |
| Other | Power | 12V/6A |
| | dimension | 440mm(length)* 400.5mm(width)* 60mm(height) |