

## IP Camera HR2 Series



### Model :

IPC-HR25110PE-IR5、IPC-HR25313PE-IR5、IPC-HR25313PL-IR5、IPC-HR25320PL-IR5

### Feature:

- High resolution 720P/960P/1080P, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed (such as:ID、 IP、 DDNS and so on)
- Advanced video compression, achieving ultra-low bit-rate, superb high-definition picture quality
- support various mobile long-distance monitoring(ios, Android)
- Support multiple web browsers(IE、 Chrome、 Firefox、 Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- Support HVR/NVR connection, support ONVIF standard

### Specifictio:

Model	IPC-HR25110PE-IR5	IPC-HR25313PE-IR5	IPC-HR25313PL-IR5	IPC-HR25320PL-IR5
-------	-------------------	-------------------	-------------------	-------------------

Image sensor	1/4" CMOS sensor	1/3" Ultra -low illumination CMOS sensor	1/3" Ultra -low illumination CMOS sensor	1/2.9" Ultra -low illumination CMOS sensor
Min.illumination	Color :0.01Lux @(F1.2,AGC ON),0 LUX with IR Black/white 0.001 Lux @(F1.2,AGC ON),0 LUX with IR			
Shutter	1/50(1/60)s to 1/10,000s			
Lens	HD professional lens3.6mm@ F1.8 (6mm option)			
Lens mount	M12			
Day/night	Support IR-CUT			
Video compression	H.264 main Profile, JPEG snapshot			
Bite rate	32 Kbps~6Mbps			32 Kbps~8Mbps
Audio compression	G.711a			
Max.image reolution	1280*720	1280*960	1280*960	1920*1080
Frame rate	50Hz:25fps (1280*720) 60Hz:25fps (1280*720)	50Hz:20fps(1280*960) ,25fps(1280*720) 60Hz:20fps(1280*960) ,25fps(1280*720)	50Hz:25fps(1280*960) 0) 60Hz:30fps(1280*960) 0)	50Hz:25fps (1920*1080) 60Hz:30fps (1920*1080)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client software.			
Storage	Network storage			
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts			
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6 option)			
Basic	anti-flicker, dual-stream, heartbeat, password protection			
Network inferface	1 * RJ45 10M/100M adaptive ethernet port			
Audio Interface	No		1ch 3.5mm JACK	

Working condition	-10°C~60°C, humidity less than 90%( non-condensing)
Power supply	DC12V±10%
Protection rang	IP66
IR distance	"IR5":50-60 meters;
Dimension	Φ 118mm*115mm
Weight	About249g