


NBD7904T-Q
Features:

- Support VGA, HDMI 1080P full HD output simultaneously;
- Support ONVIF,access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G,WIFI,IP searches, Alarm Center, etc.);


Technical Parameters:
Model: NBD7904T-Q

	Model	NBD7904T-Q
System	Main processor	Hi3535
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4
Video	Video input (IP)	4*3M
	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.264
	Display quality	Max 1920*1080
	Playback quality	3M
	Decode	4*3M
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Support
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	4*3M
	Search mode	Search by Time/Calendar/Event/Channel
Storage & Backup	Space occupation	Video: CIF 4~5G/day*channel, D1 8~10G/day*channel; 960H 12G~20G/day*channel; 720P 20~30G/day*channel; 1080P ~40G/day*channel; Audio: 691.2M/day*channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI output
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port ,4 POE ports Support POE power supply
	USB interface	2*USB2.0 ports(reserve 2 front interface)
	HDD	2 SATA(Up to 8TB for each disk)
	PTZ control	Control PTZ device by network
General	ONVIF	Support
	Power supply	48V/1.5A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kp
	Dimension	211mm(L)*86mm(W)
	Weight	Around 150g