

JF-NVR6804TR-PL



Features:

- support multiple high-definition network camera access;
- support VGA, HDMI 1080P full HD output simultaneously;
- supporting web, CMS, MYEYE platform, provide SDK development;
- supports multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);
- support ONVIF & GB28181;
- support several mobile system (iOS, Android);
- supports multiple web browser access (IE, Chrome, Firefox Safari);
- more than twenty languages;
- perfect protection circuit, unique triple watchdog function

Parameters:

	Model	JF-NVR6804TR-PL
System	Main processor	Hi3515C
	Operating system	Embedded LINUX
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4
Audio & video	Standard	Video: PAL, NTSC; Audio: G.711a
	Decode	H.264
	Monitor quality	MAX: 1920*1080
	Playback quality	1080P/D1
	Video input	4*1080P/8*D1
	Motion detection	Depend on camera
	Intercom	Unsupport
Video playback	Record mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	1*1080P/4*D1
	Search mode	Search by time/calendar/event/channel
	Record storage	HDD, Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video out	1chVGA
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M adaptive Ethernet port
	PTZ control	control PTZ by network
	USB	2*USB2.0 ports
	HDD	1SATA (up to 6TB for each disk)
General	ONVIF	Support
	Humidity	0℃-+55℃ 10%-90% RH
	Weight	Around 1KG
	Power supply	12V/2A
	Dimension	255(L)*236mm(W)*44mm(H)

Model:

JF-NVR6804TR-PL

Interface:

