

## NVR6008T-PL



### Features:

- Support multiple high-definition network camera access; up to 1080P
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3g, wifi, IP searches, Alarm Center, etc.);
- Support ONVIF & GB28181;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely, built-in ARSP, remote monitoring by one step

### Parameters:

	<b>Model</b>	<b>NVR6008T-PL</b>
System	Main processor	Hi3520D
	Operating system	Embedded Linux
	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Interface	Preview	1/4/8
	Video input	8*1080P/8*720P
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	1080P/720P
	Standard	Video: PAL, NTSC; Audio: G.711A
	Motion detection	Support (depend on camera)
Audio& video	Intercom	Unsupport
	Record mode	Manual > Alarm > Dynamic Detection > Timing
	Local playback	2*1080P; 4*720P
	Search mode	Search by time/calendar/event/channel
	Record storage	HDD, Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
Video playback	Video out	1ch BNC, 1ch VGA, 1ch HDMI
	Audio I/O	0/1
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M adaptive Ethernet port
	PTZ control	Control PTZ by network
	USB interface	2*USB 2.0 ports
	HDD	1*SATA (Max 6 for each )
External interface	ONVIF	Support
	GB28181	Optional
	Work environment	Temperature: 0°C - +55°C, Humidity: 10% - 90%RH, Atm: 86kpa - 106kpa
	Weight	Around 1KG
	Power supply	12V/2A
	Dimension	255(L)* 236mm(W)* 44mm(H)
General		

### Model:

**NVR6008T-PL**

### Interface:

