

NVR7124K-P



Features:

- Support multiple high-definition network camera access; up to 1080P
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3g, wifi, IP searches, Alarm Center, etc.);
- Support ONVIF ;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely,built-in ARSP,remote monitoring by one step

Parameters:

	Model	NVR7124K-P
System	Main processor	Hi3535
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation
	Preview	1/4/8/16/24/32
Audio&video	Video input	8*5M/16*3M/ 24、16、8*1080P/32*960P/16*720P
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	5M/3M/1080P/960P/720P
	Standard	Video: PAL, NTSC; Audio:G.711A
	Motion detection	Depend on camera
	Intercom	Support
Record & Backup	Record mode	Manual>Alarm>Dynamic Detection>TimingDetection>Timing
	Local playback	2*5M/4*3M/4、8、8*1080P/8*960P/16 路 720P
	Search mode	Search by time/calendar/event/channel
	Record storage	HDD, network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video out	1ch VGA, 1ch HDMI
	Audio I/O	1/1
	Alarm I/O	16/4
	Network interface	1*RJ45 10M/100M/1000M ,Adaptive Ethernet port
	PTZ control	Control PTZ by network
	USB interface	2*USB2.0,1USB3.0 ports
	HDD	8*SATA (Max 6T for each), 1*ESATA
General	ONVIF	Support
	GB28181	Optional
	Work environment	Temperature:0°C~+55°C , Humidity:10%—90%RH , Atm:86kpa—106kp
	Weight	Around 6KG
	Power supply	ATX power supply
	Dimension	443mm(L)* 427.5mm(W)* 92mm(H)

NVR7124K-P

Interface:

