



NBD8904T-GSC-XPOE



Feature:

- Support H.265+ encoding, ultra-low bitrates;
- Support VGA, HDMI full HD output simultaneously;
- Support 4*XPOE+4*IPC
- XPOE network port power supply
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely

Specification:

	Model	NBD8904T-GSC-XPOE
System	Main processor	Hi3520DV400
Interface	Preview	1/4/8
Video	Codec	H.265+
	Monitor quality	VGA(1080P at most);HDMI(1080P at most)
	Video Input	4*5M@12fps (XPOE); 4*4M@15fps (XPOE) 4*4M@15fps(XPOE)+4*4M@15fps(IPC)
	Playback	1*5M@6fps; 4*4M@8fps; 1*4M@8fps
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	N/A
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch/1ch
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4*XPOE+4*IPC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	192mm*85mm
	Weight	205g