


## NBD8025R-UL

25ch 5.0MP NVR Board

### Feature:

- Support HDMI 4K output VGA HD output;
- Support ONVIF; access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);

### Parameters:



Model: NBD8025R-PL

	Model	NBD8025R-PL
System	Main processor	Hi3536C
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/9/16/25
Video	Video input (IP)	8*4K/25*5M/32*1080P
	Access bandwidth	300Mbps
	Forwarding bandwidth	240Mbps
	Video compression	H.265/H.264
	Display quality	Max:4K
	Playback quality	5M/1080P
	Decode	1*4K/2*5M/4*1080P
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	1*4K/2*5M/4*1080P
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD、Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M/1000M Adaptive Ethernet port
	USB interface	2*USB2.0 ports
	HDD	2 SATA(Up to 8TB for each disk)
	ESATA	No
Serial interface	No	
Other	ONVIF	Support
	Power supply	12V/6A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0℃-+55℃, Humidity:10%—90%RH, Atm:86kpa—106kp
	Dimension	135mm*81mm
	Weight	A total of about 103g