

NVR7904T-Q/Poe



Features:

- Support multiple high-definition network camera access; up to 4*3M, 4 POE ports Support POE power supply
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.);
- Support ONVIF & GB28181;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely, built-in ARSP, remote monitoring by one step

Parameters:

| | Model | NVR7904T-Q/Poe |
|--------------------|--------------------|--|
| System | Main processor | Hi3535 |
| | Operating system | Embedded Linux |
| Interface | Operator interface | 16-bit true color graphic menu operation interface, support mouse operation |
| | Preview | 1/4 |
| Audio & video | Video input | 4*3M |
| | Decode | H.264 |
| | Monitor quality | Max 1920*1080 |
| | Playback quality | 3M |
| | Standard | Video: PAL, NTSC; Audio: G.711A |
| | Motion detection | Depend on camera |
| | Intercom | Support |
| Video playback | Record mode | Manual>Alarm>Dynamic Detection>Timing |
| | Local playback | 4*3M |
| | Search mode | Search by time/calendar/event/channel |
| | Record storage | HDD, Network |
| | Backup mode | Network backup, USB hard disk, USB burner, SATA burner |
| External interface | Output interface | 1ch VGA, 1ch HDMI |
| | Network interface | 1*RJ45 10M/100M Adaptive Ethernet port, 4 POE ports Support POE power supply |
| | Audio I/O | 1/1 |
| | Alarm I/O | 0/0 |
| | USB interface | 2*USB 2.0 ports |
| | HDD | 1SATA (Up to 6TB for each disk) |
| General | PTZ control | Control PTZ device by network |
| | ONVIF | Support |
| | GB28181 | Optional |
| | Work environment | Temperature: 0°C - +55°C, Humidity: 10% - 90%RH, Atm: 86kpa - 106kpa |
| | Weight | Around 1.2KG |
| | Power supply | 48V/1.5A |
| | power consumption | <10W (without HDD) |
| | Dimension | 255mm(L) * 236mm(W) * 44mm(H) |

Model:

NVR7904T-Q/Poe

Interface:

